


Susol
Super Solution

Aluminum Case Plug-in Busways

LS IS



Susol Busways



Challenges to the top-class product by LSIS!

Susol Busways



Super Solution

Contents:

Features	06
Basic structure	08
Application	10
Rating	11
Cross section and dimensions	12
Grounding structure	13
Busways components	14
Busways standard components	15
Busways Electrical Characteristics	22

별지 제2호						
<h1 style="margin: 0;">시 험 성 적 서</h1>						
 부산광역시 청년정책 주관 제2회 시 험 선수단						
<p style="margin: 0;">설명자료 : ->->-></p> <p style="margin: 0;">1주차 : 2008-2009 8월</p> <p style="margin: 0;">제작자 : 문-우</p>						
<p style="margin: 0;">05-480-081 경기도 여수시 서면 청년리 100-1 TEL: 030-687-0800 FAX: 030-687-0800</p>						
<p>L. 회원인 * 주 소 : 경기도 여수시 서면 청년리 100-1 * 주 소 : 경기도 여수시 서면 청년리 100-1 * 회원등급 : 2008년 8월 * 사업 등록 : 대체부수 대체부수(Grand Hotel) 2008년 3월 21일 * 사업 등록 : 청년사업 * 사업 등록 : </p>						
<p style="text-align: center;"><u>서 험 경 과</u></p>						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center; width: 33%;">서 험 항 목</th> <th style="text-align: center; width: 33%;">서 험 경 과</th> <th style="text-align: center; width: 33%;">비 고</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">비 화 시 험</td> <td style="text-align: center;">임정교관에 척할함.</td> <td style="text-align: center;">세부내용 : 척할하나 기타내용 : 척할</td> </tr> </tbody> </table>	서 험 항 목	서 험 경 과	비 고	비 화 시 험	임정교관에 척할함.	세부내용 : 척할하나 기타내용 : 척할
서 험 항 목	서 험 경 과	비 고				
비 화 시 험	임정교관에 척할함.	세부내용 : 척할하나 기타내용 : 척할				
<p style="text-align: right;">2008. 8. 26. 일</p>						
<p style="text-align: center;">2009. 8. 소재 일</p>						
<p style="text-align: center;">한국화재보험협회 부산지부 제2회 시 험 선수단 장</p>						
<p style="text-align: center;">* 상장이라는 맹고, 소송 및 기타 법적요인 등 시정동물로 리모집 사용할 수 없습니다.</p>						

 ktl <small>한국시험인증기술원</small>	<p>(주) 한국시험인증기술원 주소: 740-2221 대전광역시 대덕구 우성로 740 휴대폰: 042-1405-0485 팩스: 042-1405-0486 웹사이트: www.ktl.or.kr</p>	 정식 인증번호 : 09-1405-0485 범위 번호 : (1) / (종 2)								
<p>1. 시험성적서</p> <ul style="list-style-type: none"> - 제작 관리자 : 정석희(인장) - 품명 : 길감도 강판식 송출관 협재용 - 퍼미션번호 : 2009_01_12 <p>2. 시험성적서의 표기 용도 : 물결련비용</p> <p>3. 시험대상품목</p> <ul style="list-style-type: none"> - 제작 관리자 : 정석희 - 보유 명칭 : Steel Business - 제조업체 : 정미철강(주) - 제조번호 : 20090101 <p>4. 시험기간 : 2009. 02. 19 ~ 2009. 02. 20</p> <p>5. 시험방법 : IEC 60529:2001, KS C IEC 60529:2002</p> <p>6. 시험환경 : 15~35 °C, 21~75 %RH, 96~105 KPa</p> <p>7. 시험결과 : ICPMS</p> <p>※ 교 : 1. 시험성적서는 퍼미션을 제출한 시설로 제작된 시험결과이며, 2. 후에 퍼미션 시설 외지 설치 및 퍼미션 등 부여를 할 수 없습니다.</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 15%;">회 원</td> <td style="width: 15%;">시험과 정 번 호 :</td> <td style="width: 15%;">기증인명 및 주소 :</td> <td style="width: 15%;">기증인명 및 주소 :</td> </tr> <tr> <td colspan="2">한국시험인증기술원</td> <td colspan="2">(주)정미철강</td> </tr> </table> <p>※ 정미철강(주) 국제시험인증기술원의 [International Laboratory Accreditation Cooperation] 성장인정 협정(Mutual Recognition Arrangement)에 서명한 국가인정기구(KOCA)로부터 증정한 문서로 대체 시험결과이다.</p> <p style="text-align: center;">2009. 02. 23</p> <div style="text-align: center; margin-top: 10px;">  <p>한국산업기술시험원장 (인)</p> </div>			회 원	시험과 정 번 호 :	기증인명 및 주소 :	기증인명 및 주소 :	한국시험인증기술원		(주)정미철강	
회 원	시험과 정 번 호 :	기증인명 및 주소 :	기증인명 및 주소 :							
한국시험인증기술원		(주)정미철강								

TEST REPORT


Susol

Super Solution



- **Super** Compact size & Light weight
- **Super** Performance & Service
- **Super** Reliability & Safety
- **Super** Easy installation

Super Solution created by the combination of *Susol Busways* and other LSIS products!



- The best alternative to replace cable system
- Upgradation of electrical system for industrial facilities and buildings enlarging the electrical capacity as well as stabilizing
- Providing high quality electric energy with high efficiency


Super Features

Realization of the best performance
over 30 years experience



Compact Size

- being smaller and lighter than conventional model by 40%



Maximum capacity

- Al type upto 6000A
- Cu type upto 7500A




Insulation

- Breakdown voltage over 30kV/mm
- Batch extrusion coating system applied



Degree of protection

- IP54 or IP65



Future-oriented distribution system

Susol Busways

High stability and reliability



- High short time current capacity
Cu type: 2000A(135kA/1sec), 4000A(220kA/1sec)
- High resistance to fire: 840°C/180min
- Lower voltage drop, influence of induction and noise



Environmental friendliness and light weight




- Adoption of environmentally friendly insulator and high strength Aluminum alloy
- Reduction of the max. weight by 50% thanks to Aluminum case



Easy construction and maintenance

- Convenience of assembling by special joint pack



Options



- Grounding to aluminum case (over 100%)
- Fault monitoring system



Susol Busways



■ New concept of jointing

New assembling method using special joint pack is applied to all the Susol busways. This technology enlarges the contact area by using both surface contacting and uses only one torque value(1000kgf · cm) for all models, which result in more convenient construction and stable jointing.


Basic structure




Application

Susol

Building distribution system



Plant distribution system



Rating


Susol

Susol Busways are plug-in type insulated main bus system suitable for all power lines in low voltage industrial equipments and buildings.


Item	Rating				
Rated voltage	AC1000V/DC1500V				
Rated current	AI		630 ~ 6000A		
	Cu		630 ~ 7500A		
Rated frequency	50 / 60Hz				
Short-time withstand current	AI	2000A	121kA/1sec		
		4000A	200kA/1sec		
	Cu	2000A	135kA/1sec		
		4000A	220kA/1sec		
Wiring system	3W, 4W, 5W				
Grounding	Basic method		grounding to housing		
	Maximum capacity		over 200%		
	Grounding type		housing : over 100% Internal Type : 50/100 %		
Resistance to fire	AC 1000 V : 840°C / 180min.				
Degree of protection	Indoor	IP54			
	Outdoor	IP65			
Enclosure material	High Strength Aluminum Extrusion (Thickness : 3 mm)				
Insulation material	Poly Amide - 66 (thermoplastic)				
Conductor material	Aluminum or Copper				
Environment	Altitude	below 1000m			
	Ambient temp	-25 ~ 40°C			
	Humidity	below 97%			
Allowable temp. (IEC standard)	Housing	55K			
	Joint part	95K			
Color of painting	MUNSELL No.	5Y 7/1			
		7.5 BG 6 / 1.5			
Standard	IEC 60439 - 1, 2				

Cross section and dimensions


Susol



<Fig.1>



<Fig.2>



<Fig.3>

Al Type

Rated current (A)	Fig.	Al Busbar		3W				4W				5W			
		T (mm)	A (mm)	W (mm)	H (mm)	Weight(kg/m)		W (mm)	H (mm)	Weight(kg/m)		W (mm)	H (mm)	Weight(kg/m)	
						3W	1/2E			4W	1/2E			5W	1/2E
630	Fig.1	6.4	41×1	96	106	6.1	6.4	96	115	6.9	7.2	96	124	7.7	8.1
800			62×1	117		7.7	8.2	117		8.9	9.4	117		10.1	10.6
1000			86×1	141		9.3	10.0	141		10.9	11.6	141		12.5	13.2
1250			108×1	163		10.8	11.6	163		12.8	13.6	163		14.8	15.6
1600			164×1	219		14.6	15.9	219		17.5	18.8	219		20.5	21.7
2000			210×1	265		17.7	19.3	265		21.4	23.1	265		25.1	26.8
2500			126×2	342		23.3	25.2	342		27.9	29.8	342		32.5	34.4
3200			164×2	418		28.4	31.0	418		34.3	36.9	418		40.2	42.8
3600			184×2	458		31.1	34.0	458		37.7	40.6	458		44.2	47.1
4000			210×2	510		34.7	37.9	510		42.1	45.4	510		49.6	52.8
5000	Fig.3		184×3	677		46.3	50.7	677		56.9	60.5	677		65.9	70.2
6000			210×3	755		51.6	56.5	755		62.8	67.7	755		74.0	78.9


Cu Type

Rated current (A)	Fig.	Cu Busbar		3W				4W				5W			
		t (mm)	A (mm)	W (mm)	H (mm)	Weight(kg/m)		W (mm)	H (mm)	Weight(kg/m)		W (mm)	H (mm)	Weight(kg/m)	
						3W	1/2E			4W	1/2E			5W	1/2E
630	Fig.1	6.4	41×1	96	106	10.9	11.9	96	115	13.3	14.2	96	124	15.6	16.7
800			41×1	96		10.9	11.9	96		13.3	14.2	96		15.6	16.7
1000			57×1	112		14.0	15.5	112		17.4	18.7	112		20.7	22.1
1250			73×1	128		17.0	18.9	128		21.3	23.1	128		25.6	27.4
1600			108×1	163		23.5	26.3	163		29.7	32.7	163		36.3	39.1
2000			145×1	200		30.4	34.1	200		38.7	42.9	200		47.6	51.4
2500			195×1	250		39.6	44.7	250		50.8	56.5	250	124	62.9	68.0
3200			108×2	306		46.3	51.8	306		59.3	64.8	306		72.0	77.5
3600			126×2	342		52.9	59.5	342		68.2	74.7	342		83.0	89.5
4000			145×2	380		60.0	67.5	380		77.7	85.1	380		94.6	102.1
5000			195×2	480		78.5	88.6	480		102.5	112.5	480		125.2	135.3
6000	Fig.3		145×3	560		89.6	100.8	560		115.7	126.9	560		141.1	152.3
7500			195×3	710		117.5	132.6	710		152.9	168.0	710		187.0	202.2


Grounding structure

Susol


- Grounding function over 100% of main capacity by using aluminum extrusion material for case.
- Additional grounding function of 50% or 100% by internal type .




[3W+GE]




[3W+50%+GE]




[4W+GE]



[4W+50%+GE]



[4W(N=200%)+GE]



[4W(N=200%)+50%+GE]

Susol Busways Components

Susol

Susol Busways offer various jointing components to meet any equipments and structures.



Feeder



Feeder with Plug-in Hole



Reducer



H-Elbow



V-Elbow



V-Tee Elbow



H-Offset Elbow



V-Offset Elbow




Combination Elbow


Susol Busways Standard Components

Susol

Feeder



Plug-in Feeder




Susol Busways Standard Components

Susol

Elbow


Horizontal Elbow

Conductor	Current(A)	Dimensions(mm)	
		L1	L2
Al	Total		500
Cu			




Vertical Elbow

Conductor	Current(A)	Dimensions(mm)	
		L1	L2
Al	630~1250	400	
	1600~2500	500	
	3200~4000	600	
	5000~6000	700	
Cu	630~2000	400	
	2500~4000	500	
	5000~6000	600	
	7500	700	




Vertical Tee Elbow

Conductor	Current(A)	Dimensions(mm)		
		L1	L2	L3
Al	630~1250	400		
	1600~2500	500		
	3200~4000	600		
	5000~6000	700		
Cu	630~2000	400		
	2500~4000	500		
	5000~6000	600		
	7500	700		




Horizontal Offset Elbow

Conductor	Current(A)	Dimensions(mm)	
		L1	L2
Al	Total		500
Cu			




Vertical Offset Elbow

Conductor	Current(A)	Dimensions(mm)		
		L1	L2	L3
Al	630~1250		400	
	1600~2500		500	
	3200~4000		600	
	5000~6000		700	
Cu	630~2000		400	
	2500~4000		500	
	5000~6000		600	
	7500		700	



Combination Elbow

Conductor	Current(A)	Dimensions(mm)		
		L1	L2	L3
Al	630~1250		400	
	1600~2500		500	
	3200~4000		600	
	5000~6000		700	
Cu	630~2000		400	
	2500~4000		500	
	5000~6000		600	
	7500		700	




Susol Busways Standard Components

Susol


Reducer

Conductor	Current(A)	Dimensions(mm)		
		L1	L2	L3
AI	630~2000	500	500	1000
	2500~4000	500	600	1100
	5000~6000	500	750	1250
Cu	630~2500	500	500	1000
	3200~5000	500	600	1100
	6000~7500	500	750	1250




Flange End

630~2500A : 1 Stack




No.	Rated current(A)		(Note) Fig.	Dimensions(mm)										
	AI	Cu		A(3W)	A(4W)	A(5W)	B	C	D(3W)	D(4W)	D(5W)	F	G	G-Bus
1	630	630, 800	Fig.1	250	350	450	96	126	110	160	210	41	-	3t × 25
2	-	1000					112	142				57	-	
3	800	-					117	147				62	-	
4	-	1250	Fig.2	250	350	450	128	158	110	160	210	73	40	6t × 25
5	1000	-					141	171				86	40	
6	1250	1600					163	193				108	50	
7	-	2000	Fig.3	250	350	450	200	230	110	160	210	145	50	6t × 25
8	1600	-					219	249				164	40	
9	-	2500					250	280				195	50	
10	2000	-	Fig.4	250	350	450	265	295				210	50	

Note : See the detail of terminal busbar




2500~5000A : 2 Stack




No.	Rated current(A)		Fig.	Dimensions(mm)										
	AI	Cu		A(3W)	A(4W)	A(5W)	B	C	D(3W)	D(4W)	D(5W)	F	G	G-Bus
1	-	3200	Fig. 2	310	440	570	306	168	140	205	270	108	50	6t×40
2	2500	3600					342	186				126	40	
3	-	4000					380	205				145	50	
4	3200	-					418	224				164	40	
5	3600	-					458	244				184	45	
6	-	5000					480	255				195	50	
7	4000	-					510	270				210	50	

Note : See the detail of terminal busbar




5000~7500A : 3 Stack




No.	Rated current(A)		Fig.	Dimensions(mm)										
	AI	Cu		A(3W)	A(4W)	A(5W)	B	C	D(3W)	D(4W)	D(5W)	F	G	H
1	-	6000	Fig. 3	310	440	570	560	195	140	205	270	145	50	200
2	5000	-					677	234				184	45	239
3	-	7500					710	245				195	50	250
4	6000	-					755	260				210	50	265

Note : See the detail of terminal busbar



Detail of terminal busbar




Susol Busways Standard Components

Susol

Flange


Floor Type

No.	Rated current(A)		Dimensions(mm)
	AI	Cu	
1	630	630, 800	116
2	-	1000	132
3	800	-	137
4	-	1250	148
5	1000	-	161
6	1250	1600	183
7	-	2000	220
8	1600	-	239
9	-	2500	270
10	2000	-	285
11	-	3200	326
12	2500	3600	362
13	-	4000	400
14	3200	-	438
15	3600	-	478
16	-	5000	500
17	4000	-	530
18	-	6000	580
19	5000	-	697
20	-	7500	730
21	6000	-	775




Wall Type

No.	Rated current(A)		Dimensions(mm)
	AI	Cu	
1	630	630, 800	156
2	-	1000	172
3	800	-	177
4	-	1250	188
5	1000	-	201
6	1250	1600	223
7	-	2000	260
8	1600	-	279
9	-	2500	320
10	2000	-	325
11	-	3200	366
12	2500	3600	402
13	-	4000	440
14	3200	-	478
15	3600	-	518
16	-	5000	540
17	4000	-	570
18	-	6000	620
19	5000	-	737
20	-	7500	770
21	6000	-	815



Joint Detail



Susol Busways Electrical Characteristics

Susol

Short-time current capacity and impedance

Aluminum Conductor

Conductor	Stack	Current(A)	Short-time current capacity(kA/1sec)	Impedance Data (X10 ⁻⁵ Ω/m)		
				R	X	Z
Al	1	630	20	14.06	3.83	14.57
		800	35	9.19	3.28	9.76
		1000	50	6.59	2.29	6.97
		1250	60	5.23	2.10	5.63
		1600	95	3.43	1.57	3.77
		2000	121	2.67	0.95	2.84
	2	2500	140	2.24	0.85	2.39
		3200	170	1.71	0.79	1.89
		3600	180	1.53	0.75	1.70
		4000	200	1.34	0.46	1.41
	3	5000	200	1.02	0.35	1.08
		6000	200	0.89	0.31	0.94

Copper Conductor

Conductor	Stack	Current(A)	Short-time current capacity(kA/1sec)	Impedance Data (X10 ⁻⁵ Ω/m)		
				R	X	Z
Cu	1	630	35	8.00	3.93	8.91
		800	35	8.00	3.93	8.91
		1000	50	5.70	3.11	6.49
		1250	65	4.42	2.56	5.11
		1600	95	2.97	1.64	3.39
		2000	135	2.21	1.25	2.54
	2	2500	150	1.64	0.89	1.86
		3200	190	1.49	1.02	1.80
		3600	200	1.27	0.88	1.55
		4000	220	1.10	0.75	1.33
	3	5000	220	0.82	0.56	0.99
		6000	220	0.74	0.50	0.89
		7500	220	0.55	0.37	0.66

Voltage drop

Aluminum Conductor

(Unit : Volt/100m)

Conductor	Stack	Current(A)	Busbar Size (mm)		Power Factor(%)					
			Thickness	Wide	0.5	0.6	0.7	0.8	0.9	1.0
Al	1	630	6.40	41	11.29	12.55	13.73	14.78	15.63	15.34
		800		62	10.30	11.28	12.16	12.92	13.44	12.74
		1000		86	9.14	10.02	10.82	11.50	11.99	11.41
		1250		108	9.60	10.43	11.17	11.78	12.17	11.32
		1600		164	8.52	9.18	9.76	10.21	10.44	9.50
		2000		210	7.48	8.19	8.83	9.38	9.76	9.25
	2	2500		126	8.03	8.75	9.41	9.95	10.32	9.68
		3200		164	8.54	9.20	9.78	10.23	10.46	9.50
		3600		184	8.81	9.45	10.00	10.42	10.60	9.51
		4000		210	7.39	8.10	8.75	9.32	9.72	9.25
	3	5000		184	7.03	7.71	8.33	8.87	9.25	8.81
		6000		210	7.42	8.13	8.78	9.34	9.73	9.25

Copper Conductor

(Unit : Volt/100m)

Conductor	Stack	Current(A)	Busbar Size (mm)		Power Factor(%)					
			Thickness	Wide	0.5	0.6	0.7	0.8	0.9	1.0
Cu	1	630	6.40	41	8.08	8.67	9.17	9.55	9.72	8.73
		800		41	10.26	11.00	11.64	12.13	12.35	11.08
		1000		57	9.60	10.23	10.75	11.13	11.23	9.87
		1250		73	9.59	10.18	10.66	10.99	11.04	9.58
		1600		108	8.05	8.58	9.01	9.32	9.39	8.24
		2000		145	7.57	8.05	8.44	8.71	8.77	7.64
	2	2500		195	6.88	7.34	7.71	7.98	8.06	7.09
		3200		108	9.01	9.46	9.80	9.98	9.88	8.24
		3600		126	8.72	9.15	9.47	9.63	9.53	7.93
		4000		145	8.32	8.74	9.06	9.23	9.14	7.64
	3	5000		195	7.74	8.13	8.42	8.58	8.49	7.09
		6000		145	8.32	8.74	9.06	9.23	9.14	7.64
		7500		195	7.71	8.10	8.39	8.55	8.47	7.09